

Part Number	Package	Polarity	Configuration	ESD (Y/N)	V _{DS} (V)	V _{GS} (V)	V _{GS(TH)} (V)			R _{DS(ON)} (max. mΩ) @ V _{GS} =10V
							Min.	Typ.	Max.	
SI-CF023N65AW3	TO-247	N	Single	N	650V	±30	2.5	3	3.5	23
SI-CM032N65AW3	TO-247	N	Single	N	650V	±30	2.5	3	3.5	32
SI-CF034M65AW3	TO-247	N	Single	N	650V	±30	2.5	3	3.5	34
SI-CM041M65AW3	TO-247	N	Single	N	650V	±30	2.5	3	3.5	41
SI-CM75M65AW3	TO-247	N	Single	N	650V	±30	2.5	3	3.5	75
SI-CM105M65AW3	TO-247	N	Single	N	650V	±30	2.5	3	3.5	105
SI-CM105M65AB	TO-263	N	Single	N	650V	±30	2.5	3	3.5	105
SI-CM105M65AW	TO-220C	N	Single	N	650V	±30	2.5	3	3.5	105
SI-CM105M65AHF	TO-220F	N	Single	N	650V	±30	2.5	3	3.5	105
SI-CM105M65AB	TO-263	N	Single	N	650V	±30	2.5	3	3.5	105
SI-CM105N60AD8	DFN8*8	N	Single	N	600V	±30	2.5	3	3.5	105
SI-CM125M65AW3	TO-247	N	Single	N	650V	±30	2.5	3	3.5	125
SI-CM125M65AHF	TO-220F	N	Single	N	650V	±30	2.5	3	3.5	125
SI-CM125M65AB	TO-263	N	Single	N	650V	±30	2.5	3	3.5	125
SI-CM125M65AHC	TO-220C	N	Single	N	650V	±30	2.5	3	3.5	125
SI-CM125M65AD8	DFN8*8	N	Single	N	650V	±30	3.5	4	4.5	125
SI-CE125N60AD8	DFN8*8	N	Single	Y	650V	±30	3.5	4	4.5	125
SI-CM190N65AM0	TO-252	N	Single	N	650V	±30	3.5	4	4.5	190
SI-CM190M65AW	TO-247	N	Single	N	650V	±30	3.5	4	4.5	190
SI-CM190M65AHF	TO-220F	N	Single	N	650V	±30	3.5	4	4.5	190
SI-CM190M65AB	TO-263	N	Single	N	650V	±30	3.5	4	4.5	190
SI-CM190M65AHC	TO-220C	N	Single	N	650V	±30	3.5	4	4.5	190
SI-CM190M65AD8	DFN8*8	N	Single	N	650V	±30	3.5	4	4.5	190

SI-CM280M65AP5	PDFN5*6	N	Single	N	650V	±30	3.5	4	4.5	280
SI-CM280M65AW	TO-247	N	Single	N	650V	±30	3.5	4	4.5	280
SI-CM280M65AM0	TO-252	N	Single	N	650V	±30	3.5	4	4.5	280
SI-CM280M65AHF	TO-220F	N	Single	N	650V	±30	3.5	4	4.5	280
SI-CM280M65AB	TO-263	N	Single	N	650V	±30	3.5	4	4.5	280
SI-CM280M65AHC	TO-220C	N	Single	N	650V	±30	3.5	4	4.5	280
SI-CM280M65AF0	TO-251	N	Single	N	650V	±30	3.5	4	4.5	280
SI-CM280M65AD8	DFN8*8	N	Single	N	650V	±30	3.5	4	4.5	280
SI-CM280N60AD8	DFN8*8	N	Single	N	650V	±30	3.5	4	4.5	280
SI-CE340N65AP5	PDFN5*6	N	Single	Y	650V	±30	3	3.5	4	340
SI-CE340M65AM0	TO-252	N	Single	Y	650V	±30	3	3.5	4	340
SI-CE340M65AHF	TO-220F	N	Single	Y	650V	±30	3	3.5	4	340
SI-CE340M65AB	TO-263	N	Single	Y	650V	±30	3	3.5	4	340
SI-CE340M65AHC	TO-220C	N	Single	Y	650V	±30	3	3.5	4	340
SI-CE340M65AF0	TO-251	N	Single	Y	650V	±30	3	3.5	4	340
SI-CM340M65AD8	DFN8*8	N	Single	Y	650V	±30	3	3.5	4	340
SI-CM370M65AP5	PDFN5*6	N	Single	N	650V	±30	3.5	4	4.5	370
SI-CM370M65AM0	TO-252	N	Single	N	650V	±30	3.5	4	4.5	370
SI-CM370M65AHF	TO-220F	N	Single	N	650V	±30	3.5	4	4.5	370
SI-CM370M65AB	TO-263	N	Single	N	650V	±30	3.5	4	4.5	370
SI-CM370M65AHC	TO-220C	N	Single	N	650V	±30	3.5	4	4.5	370
SI-CM370M65AF0	TO-251	N	Single	N	650V	±30	3.5	4	4.5	370
SI-CM370M65AD8	DFN8*8	N	Single	N	650V	±30	3.5	4	4.5	370
SI-CM600M65AP5	PDFN5*6	N	Single	N	650V	±30	3.5	4	4.5	600
SI-CM600M65AM0	TO-252	N	Single	N	650V	±30	3.5	4	4.5	600
SI-CM600M65AHF	TO-220F	N	Single	N	650V	±30	3.5	4	4.5	600
SI-CM600M65AB	TO-263	N	Single	N	650V	±30	3.5	4	4.5	600

SI-CM600M65AHC	TO-220C	N	Single	N	650V	±30	3.5	4	4.5	600
SI-CM600M65AF0	TO-251	N	Single	N	650V	±30	3.5	4	4.5	600
SI-CM600M65AD8	DFN8*8	N	Single	N	650V	±30	3.5	4	4.5	600
SI-CM950M65AP5	PDFN5*6	N	Single	N	650V	±30	3.5	4	4.5	950
SI-CM950M65AM0	TO-252	N	Single	N	650V	±30	3.5	4	4.5	950
SI-CM950M65AHF	TO-220F	N	Single	N	650V	±30	3.5	4	4.5	950
SI-CM950M65AB	TO-263	N	Single	N	650V	±30	3.5	4	4.5	950
SI-CM950M65AHC	TO-220C	N	Single	N	650V	±30	3.5	4	4.5	950
SI-CM950M65AF0	TO-251	N	Single	N	650V	±30	3.5	4	4.5	950
SI-CM950M65AD8	DFN8*8	N	Single	N	650V	±30	3.5	4	4.5	950
SI-CM950M65AP3	PDFN3*3	N	Single	N	650V	±30	3.5	4	4.5	950